

LF-PSF1009B

24-Port PoE 10/100Mbps



Features

- 24 x 10/100Mbps Ethernet Port support IEEE 802.3af/at PoE
- PoE power up to 300W for all PoE ports, IEEE 802.3af: 15.4w, IEEE 802.3at: 30w
- Supports IEEE 802.3x flow control for Full-duplex Mode and backpressure for Half-duplex Mode
- 8K entry MAC address table of the with auto-learning and auto-aging
- LED indicators for monitoring power, link, activity
- External power adapter supply

Description

LF-PSF1009B is a 24 10/100Mbps ports unmanaged switch that requires no configuration and provides 24 PoE (Power over Ethernet) ports. It can automatically detect and supply power with all 24V compliant Powered Devices (PDs). In this situation, the electrical power is transmitted along with data in one single cable allowing you to expand your network to where there are no power lines or outlets, where you wish to fix devices such as APs, IP Cameras or IP Phones, etc.

Easy To Use

LF-PSF1009B is easy to install and use. It requires no configuration and installation. With desktop design, outstanding performance and quality, the 24-Port 10/100Mbps Desktop Switch with 24-Port PoE is an ideal choice for expanding your home or office network.

Specifications

Hardware	
Standard	IEEE 802.3u, IEEE802.3x, IEEE 802.3 i 10 BASE-t
Interface	24 10/100Mbps RJ45 Ports AUTO Negotiation/AUTO MDI/MDIX 2 10/100/1000Mbps RJ45 Uplink 2 SFP Slot
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100 STP (maximum 100m) 100BASE-TX: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100 STP (maximum 100m)
PoE Ports	PoE Type : IEEE 802.3af/at PoE, PoE Ports: Port1- Port24
Power Supply	300w, IEEE 802.3af: 15.4w, IEEE 802.3at: 30w
Backbound	4.8Gbps
Mac Address Table	8K
External Power Supply	External Power Adapter
Fan Quantity	None
Hardware	
Transmission Method	Store-And-Forward
Package Contents	Switch, Power Adapter, User Guide
Operating Temperature	0°C~40°C (32°F~104°F)
Storage Temperature	-40°C~70°C (-40°F~158°F)
Relative Humidity	10% ~ 90%, Non-condensing
Storage Humidity	5%~95%, Non-condensing
Certifications	CE,FCC, ROHS