

## LF-PSG1005B

5-Port PoE

10/100/1000Mbps Switch



### Features

- 4 x 10/100/1000Mbps Ethernet Port support IEEE 802.3af/at PoE
- PoE power up to 72W for all PoE ports, IEEE 802.3af: 15.4w, IEEE 802.3at: 30w
- Supports IEEE 802.3x flow control for Full-duplex Mode and backpressure for Half-duplex Mode
- 2K entry MAC address table of the with auto-learning and auto-aging
- LED indicators for monitoring power, link, activity
- External power adapter supply

### Description

LF-PSG1005B is an 5 10/100/1000Mbps ports unmanaged switch that requires no configuration and provides 4PoE (Power over Ethernet) ports. It can automatically detect and supply power with all IEEE 802.3af/at compliant Powered Devices (PDs). In this situation, the electrical power is transmitted along with data in one single cable allowing you to expand your network to where there are no power lines or outlets, where you wish to -fix devices such as APs, IP Cameras or IP Phones, etc.

### Easy To Use

LF-PSG1005B is easy to install and use. It requires no configuration and installation. With desktop design, outstanding performance and quality, the 5-Port 10/100/1000Mbps Desktop Switch with 4-Port PoE is an ideal choice for expanding your home or office network.

## Specifications

Hardware	
Standard	IEEE 802.3u, IEEE802.3x, IEEE 802.3 i 10 BASE-t
Interface	4 10/100/1000Mbps RJ45 Ports 1 10/100/1000Mbps RJ45 Uplink 1 SFP Slot
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100 STP (maximum 100m) 100BASE-TX: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100 STP (maximum 100m)
PoE Ports	PoE Type : IEEE 802.3af/at PoE, PoE Ports: Port1- Port4
Power Supply	72w, IEEE 802.3af: 15.4w, IEEE 802.3at: 30w
Backbound	10Gbps
Mac Address Table	2K
External Power Supply	External Power Adapter
Fan Quantity	None
Hardware	
Transmission Method	Store-And-Forward
Package Contents	Switch, Power Adapter, User Guide
Operating Temperature	0°C~40°C (32°F~104°F)
Storage Temperature	-40°C~70°C (-40°F~158°F)
Relative Humidity	10% ~ 90%, Non-condensing
Storage Humidity	5%~95%, Non-condensing
Certifications	CE,FCC, ROHS